



LCM-4 Series Roller Tightener



- Industry leading 3 year warranty*.
- Deprag German air motor. Lubrication free capable.
- Omron sensors and HMI
- Variable torque adjustment through regulator.
- Tool free changeovers
- Capable of handling a large variety bottle and cap sizes with appropriate change parts.
- Festo/SMC Pneumatics.
- Bottle/Jar clamps for 1 product included.
- Max cycle speed 45/min. (Product Dependant)
- All external metal parts and frames from 304 stainless steel and anodised aluminium.
- Chucks can be used instead of the rollers by utilizing the included central spindle which gives you maximum versatility for cap types. Chucks not included in price. Chuck prices vary
- Fully interlocked safety guards are available for additional cost

- Our roller tighteners use only the most high quality components. German and Japanese Pneumatics. The Deprag air motor is capable of running lubrication free.

- Our capper frames are freestanding so they can be easily moved around. The HMI can display important features such as cycle speed and product count.

- Machine suitable for all industries: Beverage, Pharmaceutical, Food, Chemical.

- *Warranty, terms and conditions of sale to be supplied with quotation.

MACHINE SPECIFICATIONS	
Length	650mm
Width	650mm
Height	1.8m
Weight	165kg
Air Requirements	6-8 Bar
Electrical Requirements	240V